


TIRE SERVICE RECORD FOR FALKEN BRAND RADIAL TIRES

Falken Tires
8656 Haven Ave.
Rancho Cucamonga, CA 91730

*Dealer: The data of each service category should be checked in the appropriate space.
Include odometer reading, date performed and dealership name performing the service.*

MILES / KM	ROTATION	ALIGNMENT	BALANCE	ODOMETER	DEALERSHIP
5,000 / 8,000					
10,000 / 16,000					
15,000 / 24,100					
20,000 / 32,100					
25,000 / 40,200					
30,000 / 48,200					
35,000 / 56,300					
40,000 / 64,300					
45,000 / 72,400					
50,000 / 80,400					
55,000 / 88,400					
60,000 / 96,500					
65,000 / 104,600					
70,000 / 112,600					
75,000 / 120,700					
80,000 / 128,700					

IMPORTANT: THIS RECORD MUST BE MAINTAINED IN ORDER TO QUALIFY FOR THE LIMITED MILEAGE WARRANTY.



TIRE PURCHASER

Tire Size _____

Car Make / Model _____

Name _____

Street _____

State _____ ZIP Code _____

DEALER

Name _____

Street _____

State _____ ZIP Code _____

DOT SERIAL NUMBER RECORD AND ODOMETER READINGS

DOT Serial Number:

Odometer Readings: _____

On _____ On Date _____

Off _____ Off Date _____

DOT Serial Number:

Odometer Readings: _____

On _____ On Date _____

Off _____ Off Date _____

DOT Serial Number:

Odometer Readings: _____

On _____ On Date _____

Off _____ Off Date _____

DOT Serial Number:

Odometer Readings: _____

On _____ On Date _____

Off _____ Off Date _____

DOT Serial Number:

Odometer Readings: _____

On _____ On Date _____

Off _____ Off Date _____

DOT Serial Number:

Odometer Readings: _____

On _____ On Date _____

Off _____ Off Date _____

DOT Serial Number:

Odometer Readings: _____

On _____ On Date _____

Off _____ Off Date _____

FALKEN TIRES LIMITED WARRANTY

I. Tires Covered by this Warranty:
This limited warranty applies to FALKEN brand steel-belted radial passenger car and selected light truck tires bearing the complete description and serial number as required by the DOT. This warranty applies to all FALKEN branded PCR & LTR products stamped with a 2026 production date or newer. Tires produced before 2026 are subject to previously published warranties. This warranty is effective only to tires for which claims are made within six years of date of production, based on the tire DOT serial number.

II. What is Warranted and for How Long:

A. Material and Workmanship Warranty:

- Every FALKEN brand radial tire is warranted against defects in material and workmanship for the usable life of the original tread within six years of date of production (for 2026 produced and newer) based on the tire DOT serial number. The usable life of the original tread ends at the appearance of the treadwear indicators at 3/32" (1.6mm) remaining tread depth.
- If a tire becomes unserviceable due to such defect within the first 3/32" (1.6mm) of wear, it will be replaced free of charge with a comparable FALKEN tire.
- After the first 3/32" (1.6mm) wear, a prorated adjustment credit to the customer will be given based on the percentage of remaining usable tread depth, down to the remaining 3/32" (1.6mm) wear bars, at which point no credit is due.
- OUT-OF-ROUND or OUT-OF-BALANCE claims will be accepted for adjustment only during the first 3/32" (1.6mm) of the original tread depth, and tires will be replaced free of charge with comparable FALKEN tires. A set of four (4) tires from the same vehicle will not be accepted for out-of-round or out-of-balance claims.

B. Limited Tread Life Warranty:
Most FALKEN brand tires come with a tread life warranty. Prorated adjustment credit will be given based on percentage of mileage not achieved on tires.

FALKEN brand radial tires listed below are warranted to achieve the following mileages before becoming worn out at 3/32" (1.6mm) remaining tread depth:

Passenger Car Tires:	Miles / km
SINCERA SN201 A/S (All Sizes).....	65,000 / 105,000
SINCERA SN250 A/S (Speed Ratings H, V).....	75,000 / 120,000
SINCERA SN250 A/S (Speed Rating T).....	80,000 / 130,000
ZIEX ZE950 A/S (600-A-A UTQG/H&V Rated).....	65,000 / 105,000
ZIEX ZE950 A/S (500-A-A UTQG/W Rated).....	45,000 / 70,000
ZIEX ZE960 A/S (Speed Ratings H, V).....	65,000 / 105,000
ZIEX ZE960 A/S (Speed Rating W).....	45,000 / 70,000
AKLIMATE.....	65,000 / 105,000
AZENIS FK460 A/S (All Sizes, including Silent Core).....	50,000 / 80,000
AZENIS RT660+, RT660, RT615K+, FK510.....	No Tread Life Warranty
ESPIA EPZ II, EUROWINTER HS01, WINTERPEAK F-ICE 1.....	No Tread Life Warranty

Light Truck, SUV and CUV Tires:

RUBITREK A/T (All Sizes).....	55,000 / 90,000
WILDPEAK A/T4W (Non-LT Sizes).....	65,000 / 105,000
WILDPEAK A/T4W (LT Sizes).....	60,000 / 95,000
WILDPEAK A/T3W (All Sizes).....	55,000 / 90,000
WILDPEAK A/T TRAIL (All Sizes).....	65,000 / 105,000
WILDPEAK H/T (All Sizes).....	60,000 / 95,000
WILDPEAK H/T02 (Non-LT Sizes).....	70,000 / 115,000
WILDPEAK H/T02 (LT Sizes).....	50,000 / 80,000
WILDPEAK R/T (All Sizes).....	50,000 / 80,000
ZIEX S/TZ05 (All Sizes).....	50,000 / 80,000
ZIEX CT60 A/S (All Sizes).....	65,000 / 105,000
WILDPEAK M/T.....	No Tread Life Warranty
ESPIA EPZ II SUV.....	No Tread Life Warranty

This tread life warranty is applicable only for normal highway use when all of the owner's obligations listed below in Section IV are met. Warranty does not apply to any FALKEN designs not listed.

- All eligible tread life warranty claims are based on the tire being worn down evenly to the wear bars at 3/32" (1.6mm).
- Any tire with measured tread difference of 3/32" (1.6mm) or more across the tread (main circumferential tread grooves) will be considered irregularly worn and rejected.
- Any tires submitted with 5/32" (4.0mm) or more remaining tread depths will be rejected for tread life warranty claim.
- Any tires submitted with 3/32" to 5/32" (2.4mm–3.2mm) remaining mileage and tread depth to be achieved will be projected and prorated as if the tire was worn down to 3/32" (1.6mm).
- Some vehicles come from the manufacturer with "split fitments" (or a staggered setup), which refers to different tire sizes being used on the front and rear axles. Since these tires cannot be rotated in the traditional manner, the warranty on the rear axle tires will drop to 50% of the standard mileage warranty for the applicable tread design.
- All submitted mileage claims are to include proof of tire rotation; either copy of warranty card with completed rotations listed, or copies of the customer's invoice showing rotation mileage and vehicle information will be accepted.

III. What is Not Covered (Exclusions):

A. Unserviceability due to road hazard damages (cuts, snags, punctures, bruises, impact breaks, etc.), improper repair technique or materials, improper inflation, overload, irregular wear, wheel imbalance, defective vehicle mechanical components (brakes, suspension, wheels, etc.), improper suspension alignment, accident, fire, acts of God, chemical damage, damage from chain use, racing, off-road use, runflat, improper installation, vandalism, or abuse.

- Tires on any vehicle registered and normally used outside the 50 United States, Puerto Rico, and Canada.
- Tires branded "NA" or having the DOT number removed.
- Tires presented for warranty claim by someone other than the original purchaser, or tires that were transferred to another vehicle from the one upon which they were originally installed, regardless of by whom. This warranty is not transferable.
- Any tires whose failure is caused by any previous damages or repairs.
- Any cost of tire repair or retreading is not covered by this warranty and will be solely borne by the tire owner.
- The tread life warranty is not applicable if tires are used in commercial service or, determined at our discretion, have premature or irregular wear due to abusive service or defective vehicle conditions. Abusive service includes off-road use, excessive mountain road driving, racing, or passenger car tires on pick-up, RV, or utility vehicles.
- Tires that have tread siping or otherwise modified from the original design.
 - Tires that are worn beyond the last two thirty-seconds of an inch (3/32"/1.6mm) of original tread depth. Beyond this point, the tire is considered worn out and has delivered its usable tread life and there is no manufacturer's warranty regardless of its age or mileage.

IV. Owners Obligations:
At the time of purchase, the tire(s) must be properly installed, balanced, and air pressure set to the vehicle manufacturer's specifications if original equipment size, or at an air pressure adequate to carry the vehicle load if a different replacement size. At least monthly, owner must check tire air pressure with a gauge and inflate to recommended cold PSI level. Do not rely on car servicers to perform the checks. Tires must be rotated at least every 5,000 miles, or earlier if unequal wear is occurring, and proof of compliance must be recorded on the warranty card. Owner must have tires rebalanced if vibration is experienced, and alignment must be checked if unequal or rapid wear is occurring, or when scheduled by the vehicle maker. All warranty claims must be presented to an authorized FALKEN dealer. Tire owners must present their warranty card verifying mileage, proof of date and place of purchase, to make a tread life warranty claim. The name of the FALKEN dealer from whom the tires were purchased must be included on the form.

V. DISCLAIMER:
ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL BE LIMITED IN DURATION TO THE ABOVE PERIOD. TO THE EXTENT PERMITTED BY LAW, FALKEN TIRES SHALL NOT BE RESPONSIBLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, SUCH AS LOSS OF USE OF THE TIRE OR THE VEHICLE ON WHICH IT IS USED, INCONVENIENCE, OR COMMERCIAL LOSS. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, OR THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATIONS OR EXCLUSIONS MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS, WHICH VARY FROM STATE TO STATE. THIS IS THE ONLY EXPRESS WARRANTY APPLICABLE TO FALKEN BRAND TIRES, AND SUPERSEDES THE TERMS OF ANY PREVIOUS WARRANTY. FALKEN NEITHER ASSUMES NOR AUTHORIZES ANYONE TO MAKE OR ASSUME FOR IT ANY OTHER WARRANTY.

FALKEN 30-DAY FREE TRIAL RIDE PROGRAM
If for any reason (other than those listed below as not returnable conditions) you are not satisfied with your new set of four eligible Falken tires within 30 days or 1,000 miles from date of purchase (whichever comes first), you may return them to the original place of purchase for a full reimbursement (limited to the purchase price of the tires). You will be required to present the original sales invoice and receipt.

ELIGIBLE TIRES:
SINCERA SN201 A/S, SINCERA SN250 A/S, ZIEX ZE950 A/S, ZIEX ZE960 A/S, AKLIMATE, AZENIS FK460 A/S (including Silent Core), RUBITREK A/T, WILDPEAK A/T4W, WILDPEAK A/T3W, WILDPEAK A/T TRAIL, WILDPEAK H/T, WILDPEAK H/T02, WILDPEAK R/T, ZIEX S/TZ05, ZIEX CT60 A/S

- WHAT CONDITIONS ARE NOT COVERED (Exclusions)**
Your tires are not returnable if:
- They exhibit road hazards – Cuts, snags, punctures, bruises or impact breaks and any damage caused by puncture or tire repair.
 - There is tire damage or failure resulting from improper operation or maintenance, such as: Load, speed and inflation practices causing excessive operational temperatures that exceed tires' capabilities.
 - There is tire damage or failure resulting from: Mounting damage, wheel damage or defective mechanical conditions in the vehicle, extreme temperature exposure, misuse, negligence and abusive driving, such as tire spinning, racing, extended use of unpaved roads or accident damage.

NOTE: Tires must be operated in normal highway use within the U.S. and Canada. This offer does not apply to tires used in commercial service including, but not limited to, taxi cabs, police cars, emergency vehicles and non-passenger service. Tires used in racing related activities or competitive events are excluded. The offer is not-transferable and applies only to the vehicle on which the tires were originally installed.

No Falken Tire employee, retailer or dealer has the authority to make any representation, promise or agreement on the behalf of Falken Tire, other than as stated in this 30-Day Ride Guarantee Program card.



TIRE SAFETY, CARE, AND MAINTENANCE GUIDE

IMPORTANT SAFETY INFORMATION

TIRE INFLATION OVERLOADING AND TIRE LOAD CAPACITY

Serious injury or death may result from tire underinflation or overloading. Follow owner’s manual and your car’s tire information placard for proper inflation pressures and load carrying capacities.

MAINTAIN PROPER INFLATION PRESSURE IN YOUR TIRES

Proper inflation pressure is necessary for tire safety, performance, and best fuel economy. To maintain proper inflation pressure, at least monthly check your tires with an accurate pressure gauge while cool (driven less than a mile). If you check hot tires while traveling, expect the pressure to be 5–10 PSI above the recommendation. That is normal, due to temperature rise during flexing. Do not bleed off pressure to reduce pressure down to the recommendation. If a hot tire reads at or below recommended pressure, add 5 PSI more than recommended, and then later check when cool. It is very difficult to tell an underinflated tire just by looking at it—you must use a gauge. Set the pressure to the level recommended by the vehicle manufacturer for the original equipment size tire, or use FALKEN’s pressure recommendation if the size has been changed from the original equipment size.

Underinflation is the most common cause of tire failures in any kind of tire and may result in severe cracking, component separation and tire failure (“blow-out”), with unexpected loss of vehicle control, and accident, with possible death or injury.

Furthermore, when driving a vehicle with radial tires, especially low profile tires, it is very difficult to notice that a tire has started to deflate or gone flat, since the “feel” of the vehicle does not change appreciably. Therefore, frequent visual and pressure inspections are very necessary.

DO NOT OVERLOAD YOUR TIRES

Check your vehicle tire placard to determine the tire load limits. Overloading your vehicle places stress on your tires and other vehicle components. Overloading can cause tire failure, due to the same overflexing resulting from underinflation.

TIRE LOAD CARRYING CAPACITY

Replacement tires must have a load carrying capacity equal to or greater than the capacity of the original tires, at their recommended pressures. **Using the wrong size tire can lead to tire failure.**

The door mounted tire information placard shows the size, load index, and recommended pressures for each axle. While it is generally recommended that any replacement tires have the same load index as the original tires, circumstances may allow a lower load index, but only if the replacement tires can carry the same actual loads as the original tires, although at different air pressures. **Such a determination requires a sophisticated analysis of the load and inflation charts for the original and prospective replacement tires, which should be done only by a trained tire professional.** We recommend you consult with FALKEN or an authorized dealer for guidance in this area.

Additionally, Load Indexes may be “Standard” or “Reinforced.” Some Reinforced ratings will require additional air pressure to carry the same loads as Standard ratings. **Consult FALKEN or an authorized dealer for specific guidance about air pressure requirements for Reinforced Load index tires.**

LOAD INDEX

IMPORTANT REMINDER: If you require different air pressures for your new tires to carry the tire loads, you have the responsibility to ensure those pressures are ALWAYS used.

We recommend you place an additional new tire information sticker (available from FALKEN, or make your own) near your placard, with the new tire sizes and required air pressures noted, so that any maintenance persons will know there has been a change. If that is not done or you do not personally check your pressures, there is a high risk that your pressures will be set at the original requirements, and your tires will be underinflated, which can result in tire failure and accident.

TIRE UP-SIZING (“PLUS-SIZING”) GUIDELINES AND SAFETY WARNINGS

Every new vehicle sold in the USA is required to have a vehicle tire placard attached to the door edge, door jamb, or glove box, which shows the original tire size, load capacity, and recommended air pressure for the design dynamic loads on each axle.

When making a replacement tire choice, always first check your placard to get the original tire information—it is always possible that what you currently have mounted on the vehicle is not original equipment. Then, using the following FALKEN guidelines for tire replacement, choose a new tire size and load capacity that will meet or exceed the original requirements.

TIRE SPEED RATINGS

Replacement tires must have a speed rating equal to or greater than the rating of the original tires to maintain vehicle speed capability. If the replacement tires are a lower speed rating than shown on the vehicle tire placard, the vehicle speed capability is restricted to that of the replacement tires. You must choose a speed rating that meets your operating needs and ensure you do not exceed the rated speed of your tires. Also, while speed ratings are not a direct indicator of tire handling capabilities, it is generally true that a higher rating may translate to different handling characteristics. If you decrease the speed rating, you must ensure that you are familiar with the handling characteristics of your vehicle and adjust your driving to the lower rating.

DO NOT SPIN YOUR TIRES EXCESSIVELY

Avoid excessive spinning of the powered wheels when your vehicle is stuck in snow, ice, mud, or sand. Depending on your vehicle’s drive train design, it is possible for the tire to be spinning twice as fast as your speedometer indicates. **SAFETY WARNING: Never stand near or behind a tire that is spinning at high speed, such as pushing a vehicle from behind or when an on-the-car spin balancer is used.** The centrifugal forces on a free spinning tire and wheel assembly may result in tire explosion, vehicle damage, and personal injury or death. Never exceed 35 MPH (56 KPH) indicated on your speedometer. Use a gentle back and forth rocking motion to free your vehicle for continued driving.

WHEN REPLACING TIRES, ALWAYS CONSULT VEHICLE, TIRE, AND RIM MANUFACTURERS’ REQUIREMENTS FOR SAFETY

New Tires: Fit newest tires on the rear axle. If radials and nonradials must be fitted to the same vehicle, fit radials on the rear. If different tire profiles are fitted on the same vehicle, use the widest tires on the rear axle.

Snow Tires: When fitting snow tires to vehicles, always fit in sets of four, to avoid handling problems in both snow and dry road conditions. It could lead to adverse handling and loss of control, which could cause serious injury or death.

It is acceptable to use winter tires with a lower speed rating than the OE tires, but the vehicle maximum speed must be reduced to correspond with the new tires’ speed rating.

TIRE MIX USAGE

Never mix tires of different size or construction and/or type on an axle (except for temporary use spare tire). Always refer to vehicle owner’s manual for proper tire fitment.

TIRE OVERALL DIAMETER

As noted previously, vehicle manufacturers choose tires with a certain overall diameter for the particular design vehicle. Vehicle systems such as ABS, odometer speedometer, and onboard sensors and computers may be affected by a change in overall diameter. **FALKEN does not recommend use of tires that change your vehicle design criteria. If you choose a replacement tire size that exceeds your vehicle design criteria range for tire diameter, you may have to alter vehicle systems, suspension, and alignment to safely use it.**

On Sport Utility Vehicles (SUV) and light trucks, any increase in tire overall diameter, and the lifting of vehicle suspension to accommodate the larger size, may result in changes of vehicle ride height, with resultant changes in rollover characteristics, braking distances, and handling. **You must ensure any tire size and suspension changes allow you to maintain safe operating control under all driving conditions.**

NEVER MOUNT A “xx” SIZE DIAMETER TIRE ON A “xx . 5” RIM.

(Example: A 16” tire on a 16.5” rim.)

Mounting a “xx” tire on a “xx . 5” rim will most likely result in a tire explosion, which can cause serious injury or death. While it is possible to initially pass a “xx” tire over the lip or flange of a “xx.5” diameter rim, it cannot possibly position itself properly against the rim flange, which has a larger diameter. If an attempt is made to seat the bead by inflating the tire, the tire will break with explosive force.

DO NOT ATTEMPT TO MOUNT YOUR OWN TIRES.

SAFETY WARNING: Serious injury or death may result from explosion of the tire/rim assembly due to improper mounting procedures. Tires should be mounted only by properly trained persons using adequate mounting equipment. Follow manufacturer’s instructions and match bead diameter to rim diameter. Lubricate bead and rim mounting surfaces with standard tire lubricants. Do not use petroleum-based lubricants, which may deteriorate the tires.

Lock the wheel on a mounting machine or place in a safety cage for inflation. Do not exceed 40 PSI (275kPa) to seat the beads. Stand away from the tire in case of explosion. Never use a volatile substance to assist in seating the bead, as risk of tire explosion is great.

TIRE CARE AND MAINTENANCE

IMPORTANCE OF PROPER TIRE PRESSURE

Always practice proper tire inflation for OE and Plus sizes tire fitments. Tires have been known to lose up to 1 PSI (pounds per square inch) every month, so check all tires, including your spare, once a month (and before a long trip). DO NOT just compare to the PSI on your tire’s sidewall. Incorrect tire pressure can lead to tire damage and cause irregular tread wear. Please refer back to our safety section under both the Tire Load Carrying Capacity and the Proper Inflation sections for detailed information.

CHECK YOUR TIRES FOR WEAR AND DAMAGE

Always remove your tires from service when they reach ¼” (1.6mm) remaining tread depth. FALKEN tires have a tread depth indicator bar at the base of tread grooves that becomes apparent at ¼” depth. If those bars are exposed, the area will look smooth across the tread face. Excessively worn tires have decreased wet weather traction, and continued use may result in skidding and loss of control, and accident and personal injury or death. Also, they may be more susceptible to tread penetrations and possible deflation.

Frequent inspection of your tires for signs of damage and their general condition is important for safety. If you have questions about tire condition, have your dealer inspect them. Impact abrasions, penetrations, cracks, knots, bulges or unexplained air loss always require tire removal and close expert inspection.

Never perform a temporary or plug-type repair or use an inner tube as a substitute for a proper repair. Only qualified persons should repair tires.

Repairs may only be made between the tread shoulders, and be for penetrations ¼” or less in diameter. Repair only straight-through punctures, and ensure no tires are repaired that show evidence of run-low wrinkling or heat deterioration, cutting, cracking, separation, or other damage. Injuries to the sidewalls must not be repaired.

Repairs must fully seal the interior and fill the damage wound. You must use either a patch-plug combination, or separately fill the wound with rubber and put a patch in the interior, to ensure that neither air leaks out nor water enters the tire structure.

Repairs must be done from inside the tire, to ensure the tire is thoroughly inspected for secondary damage and the tire is properly sealed.

DO NOT USE PLUG REPAIRS APPLIED FROM OUTSIDE THE TIRE WITHOUT DEMOUNTING FALKEN does not endorse or warrant any particular type of repair process. The repair is entirely the responsibility of the repairer.

DO NOT APPLY SIDEWALL DRESSING OR HARSH CHEMICAL CLEANERS

FALKEN tire sidewalls are specially compounded to resist ozone and weather cracking. Use of some dressings or cleaners may degrade rubber and remove inherent ozone resistance, resulting in premature cracking or discoloration. Use a mild soap solution to clean sidewalls and white lettering, and rinse with plain water.

VEHICLE SUSPENSION, WHEEL ALIGNMENT, BALANCE, TIRE ROTATION, AND TIRE CONDITION

Lack of rotation, worn suspension parts, underinflation/overinflation, wheel imbalance, and misalignment may cause vibration and irregular tire wear. **Rotate your tires every 5,000 miles.** Directional tires should be rotated front-to-rear only, not crossed.

Speed ratings for FALKEN tires are determined for new tires using ECE 30 European Indoor Testing procedures, and may not be valid for damaged, altered, repaired, underinflated, overloaded, excessively worn, or retreaded tires.

FALKEN does not recommend the use of any of its products in excess of legal speed limits. Adverse driving conditions, such as rain, snow, or ice always require special handling care and greatly reduced speeds.

TIRE AGING

FALKEN recommends tires which have been in use for 6 years or more should be inspected regularly by a qualified tire specialist. Plus any tire that is 10 years or older from the date of manufacture, including spare tires, be replaced with new tires regardless of appearance, even if the tires have not reached the legal wear out limit.



LIMITED WARRANTY

Effective January 1, 2026

HIGH PERFORMANCE RADIAL TIRES

P-METRIC LIGHT TRUCK RADIAL TIRES

PASSENGER RADIAL TIRES

SPECIALTY LIGHT TRUCK TIRES